

# BUILT FOR THE LONG HAUL



## *Dry Freight*



### *Built to Deliver*

**RUGGED • LIGHTWEIGHT**

- Built using the best manufacturing standards available, ABC's dry freight van body offers unmatched durability and maximized performance. Its rugged, watertight construction features superior building materials.
- Your dry freight van body will provide you with long-lasting quality performance.



# Dry Freight

## Options:

- Fiberglass Reinforced Plywood (FRP) (Plywood lining is not required on FRP bodies)
- Side cargo door with stirrup step and grab handle
- Aluminum walk ramps
- Scuff plates
- Liftgates
- Cab mounted wind deflector
- Insulation
- Bumpers
- Various widths
- Cargo control devices
- Cabovers
- Interior shelving systems
- Apitong wood slats
- 102" wide body
- Hardwood, composite or pine floor
- One piece translucent roof



Galvanized anti-sag roof bows support roof and protect interior cargo from snags. While the .032 aluminum one piece roof sheet eliminates the concern of water entry.

Z-shaped side posts on 16" centers maximize contact points to exterior side panels and interior cargo control. 3/8" plywood lining on walls reduces possibility of damage from shifting loads.

3/16" solid rivets spaced 2" apart on end panel seams and 3/16" solid rivets spaced 4" apart on center panels. 4" I-beam longitudinal body sills maximize body strength.

.040 Aluminum, pre-painted white side sheets provide corrosion resistance while galvanized rear frame maximizes integrity and corrosion resistance. Complete body undercoating also included.

5" Radius extruded aluminum front corner posts and 12" aerodynamic radius front reduce wind drag while enhancing body integrity.

Rear roll-up door includes 2" nylon rollers and 1-1/8" hardwood floor with flush to floor rear entry eliminates body entry concern and provides maximum floor space.

3" Cross-members on 16" centers on bodies 18' & shorter and 3" crossmembers on 12" centers for bodies 19' & longer. All crossmembers are welded to the full perimeter steel bands for maximum strength, includes spanner plates over the rear tire area.

BODY LENGTH	INSIDE LENGTH
12'6"	144"
14'6"	168"
16'6"	192"
18'6"	216"
20'6"	240"
22'6"	264"
24'6"	288"
26'6"	312"
28'6"	336"

Model	78	84	90	96	102	108
Inside Height	78"	84"	90"	96"	102"	108"
Door Height	71.5"	77.5"	83.5"	89.5"	95.5"	101.5"

Wall to wall interior width: 76.5" SRW, 92.5" DRW. FRP bodies, add 1" to load length and 2" to load width.



Shown with standard plywood liner and optional E-track installed.



[abctruck.com](http://abctruck.com)

LOCATIONS	Columbus, OH	Cleveland, OH	Louisville, KY	Tampa, FL	Clinton, MD	Portland, OR	LaGrange, TX	WARRANTY	PARTS	CUSTOMER SERVICE
Pontiac, MI	Denver, PA	Bowmansville, PA	Reading, PA	Abington, PA	Seneca, PA	Suffolk, VA	Atlanta, GA	800.872.2831	877.349.1222	800.872.4583