



# *Dry Freight*



## *Built to Deliver*

**RUGGED • LIGHTWEIGHT**

- Built using the best manufacturing standards available, ABC's dry freight van body offers unmatched durability and maximized performance. Its rugged, watertight construction features superior building materials.
- Your dry freight van body will provide you with long-lasting quality performance.



# Dry Freight

## Options:

- Fiberglass Reinforced Plywood (FRP) (Plywood lining is not standard feature on FRP bodies)
- Side cargo door
- Aluminum walk ramps
- Scuff plates
- Liftgates
- Cab mounted wind deflector
- Insulation
- Bumpers
- Various widths
- Cargo control devices
- Cabovers
- Interior shelving systems
- Slats are a no-charge option
- 102" wide body
- Hardwood, composite or pine floor

BODY LENGTH	INSIDE LENGTH
12'6"	144"
14'6"	168"
16'6"	192"
18'6"	216"
20'6"	240"
22'6"	264"
24'6"	288"
26'6"	312"
28'6"	336"



Galvanized anti-sag roof bows support roof and protect interior cargo from snags. While the .032 aluminum one piece roof sheet eliminates the concern of water entry.

Z-shaped side posts on 16" centers maximize contact points to exterior side panels and interior cargo control. 3/8" plywood lining on walls reduces possibility of damage from shifting loads.

3/16" solid buck rivets spaced 2" apart on end panel seams and 3/16" solid buck rivets spaced 4" apart on center panels. 4" structural longitudinal body sills maximize body strength with grade 80 steel.

.040 Aluminum, pre-painted white side sheets provide corrosion resistance while galvalume rear frame maximizes integrity and corrosion resistance. Complete body undercoating also included.

5" Radius extruded aluminum front corner posts and 12" aerodynamic radius front reduce wind drag while enhancing body integrity.

Rear roll-up door includes 2" nylon rollers and 1-1/8" hardwood floor with flush to floor rear entry eliminates body entry concern and provides maximum floor space.

3" Cross-members on 16" centers on bodies 18' & shorter and 3" crossmembers on 12" centers for bodies 19' & longer. All structural crossmembers have full perimeter steel bands for strength.



- Optional translucent ceiling
- Standard fully lined 3/8" plywood walls

Model	Act 78	Act 84	Act 90	Act 96	Act 102	Act 108
Inside Height	78"	84"	90"	96"	102"	108"
Door Height	71.5"	77.5"	83.5"	89.5"	95.5"	101.5"

Wall to wall interior width: 76.5" SRW, 92.5" DRW. FRP bodies, add 1" to load length and 2" to load width.



[abctruck.com](http://abctruck.com)

LOCATIONS	Columbus, OH	Portland, OR	Washington, DC	LaGrange, TX	Pontiac, MI	WARRANTY	PARTS	CUSTOMER SERVICE
	Cleveland, OH	Louisville, KY	Philadelphia, PA	Denver, PA	Suffolk, VA	800.872.2831	877.349.1222	800.872.4583