

Marauder II



Body shown with optional equipment

Built to Last

- Marauder II offers enhanced features and value. With single side wall construction, quick release tailgate hardware and an 45,000 psi yield strength floor, Marauder II is built to last.
- Marauder II is job matched for installation on Chevy, Ford, Freightliner, GMC, Navistar, Hino and other models.
- Available in 5 through 8 yard sizes.

Marauder II

Single Wall Construction matched with Quality Components...

Options:

- Hitches
- Access ladder
- Electric trailer brake
- Strobe light
- Underbody toolbox
- Steel mudflaps
- Backpack toolbox/dump body combination
- High side board gussets
- Full length tie rail
- Tarp cover



- Hard chrome piston rod
- Lubricated bearing points
- Full length subframe

5-7 yard hoist

- Rear hinge assembly are dissimilar metals to reduce wear
- NTEA class 40
- 47° Dump angle

6-8 yard hoist

- Rear hinge assembly are dissimilar metals to reduce wear
- NTEA class 50
- 50° Dump angle



Interlaced understructure (8-gauge hi-tensile steel).

10' Models have 4 vertical side braces, two of which are corner posts.

8-Gauge hi-tensile steel fully welded body shell with single side wall construction with smooth lines.

Front corner posts and full depth rear corner posts and coal door.

Full width rear apron with double acting tailgate with quick release tailgate hardware fully braced and post mounted L.E.D. stop, turn, and taillights.

Sides radius to floor. 45,000 psi yield strength floor.

Fully boxed dirt shedder top rail.

SPECIFICATIONS

Model	CA	Length	Width	Sides	Ends	Cap (yds)	Lift Cap (tons)
Chevy, Ford, GMC, IHC	84"	10'0"	7'0"	26"	32"	5-7	13.6
Sterling, Hino, Freightliner	84"	10'0"	7'0"	28"	38"	6-8	17.1

Note: When fully loaded, total transport weight should not exceed front GAWR, rear GAWR and/or GVWR.



abctruck.com

LOCATIONS	Columbus, OH	Portland, OR	Washington, DC	LaGrange, TX	Pontiac, MI	WARRANTY	PARTS	CUSTOMER SERVICE	
	Cleveland, OH	Louisville, KY	Tampa, FL	Philadelphia, PA	Denver, PA	Suffolk, VA	800.872.2831	877.349.1222	800.872.4583